

Model 1932R

SCISSOR LIFTS



MORE ECONOMIC

- Lower Total Cost of Ownership

MORE PRODUCTIVE

- Boost efficiency with optional AGM batteries
- Improved uptime

MORE ACCESS

- Get into more places with compact dimensions and precise positioning ability for both drive and lift

SMART DESIGN

- Improved reliable, simple active pothole protection
- Unparalleled component access
- All steel components like platform and service trays

Standard Features

- Proportional Controls
- Battery Condition Indicator
- 220V-AC Receptacle in Platform
- All Motion Alarm
- 27 amp Multi-Function Universal Charger
- Horn
- Hourmeter
- Tilt Alarm and Light
- Lanyard Attach Points
- Movable, Removable Platform Control
- Nickel Plated Pins
- Lubrication Free Scissor Arm Bushings
- Scissor Maintenance Prop
- Active Pothole Protection System
- Lifting and Tie Down Points
- Fork Lift Pockets
- 36 in. (91 cm) Foot-Actuated Deck Extension
- Steel Swing-Out Doors
- Variable Tilt Window
- Manual Descent Cable
- Diamond Tread Steel Deck
- Greaseless Kingpin Joints
- Analyzer Port for Diagnostics
- Removable Ladder

Standard Specifications

- Batteries
- Charger
- Drive
- Hydraulic Reservoir Capacity
- Hydraulic Reservoir Pump
- Tire Size/Type (Non-Marking)
- Brakes
- 4 x 6V 220 amp-hr
- 27 amp High Frequency Charger
- Hydraulic Front-wheel
- 18 L
- Fixed Displacement Gear
- 323 x 100 mm
- Multi-Disc Friction



Accessories & Options

- Flashing Amber Beacon
- 220 Amp-Hour AGM Batteries
- MDI (Ground)
- Self-Closing Gate
- Anti-Vandalism Package for Ground Controls and Platform Controls
- Eagle Performance Charger
- 1,000W-AC Inverter
- Ambient Noise Alarm

Model 1932R SCISSOR LIFTS

Performance

• Working Height	7.80m
A. Platform Height - Elevated	5.80m
B. Platform Height - Lowered	0.98m
C. Platform Railing Height	1.11m
D. Stowed Height (Rails Folded)	1.64m
E. Platform Size Inside (W x L)	0.65m x 1.57m
F. Deck Extension	0.86m
G. Overall Width	0.81m
H. Overall Length	1.74m (3*)
I. Wheelbase	1.35m
J. Ground Clearance (centre of machine)	7cm
• Platform Capacity (1)	230kg (5)
• Capacity on Deck Extension	125kg
• Lift/Lower Time (no load)	24 / 29 sec.
• Maximum Drive Height	5.80m
• Machine weight (2)	1,565 kg
• Maximum Ground Bearing Pressure	8.40 kg/cm ²
• Drive Speed - Lowered	3.22 km/h
• Drive Speed - Elevated	0.80 km/h
• Gradeability	25%
• Turning Radius - Inside	0.0m
• Turning Radius - Outside	1.69m
• Tyres (Non-Marking Solid)	323 x 100
• Brakes	Hydraulic
• Drive (Nominal)	Hydraulic
• Batteries	4x 6V 220A/hr
• Charger (120/240V -50/60Hz)	24v @27Amp Automatic
• Pump Motor	4.5kW
• Hydraulic System	18L



- 1 Capacities shown are maximum with 2 persons indoor on both models.
Outdoor rating 1 Person/125kg
- 2 Certain options or country standards may increase weight and/or dimensions.
- 3* includes ladder, excluding ladder 1,67m
- 4 indoor, 250kg outdoor
- 5 indoor, 125kg outdoor

Dimensions

